

Please make the following amendments to the application:

In the Claims:

B 1 Claims 1-14 (Cancelled)

15. (Re-Presented -- formerly dependent Claim 5) A machine for injecting liquids, which comprises:

an air booster pump adapted to receive injectate; and

a head comprising a tubular wall and having apertures for nozzles, said head being in fluid communication with said air booster pump, and said tubular wall comprising a filter.

16. (Re-Presented -- formerly dependent Claim 6) A machine for injecting liquids, which comprises:

an air booster pump adapted to receive injectate; and

a plurality of heads having apertures for nozzles, each said head in fluid communication with said air booster pump.

17. (Re-Presented -- formerly dependent Claim 7) A machine for injecting liquids, which comprises:

a plurality of air pumps adapted to receive injectate; and

a plurality of heads having apertures for nozzles, each of said heads in fluid communication with one of said air booster pumps.

18. (Re-Presented -- formerly dependent Claim 10) A device for injecting liquids into a subject, said device comprising:

a reservoir for storing a fluid injectate, said reservoir having an inlet and an outlet;

an air pump having an inlet and an outlet, said air pump in fluid communication with said reservoir;

at least one injectate filter positioned between said outlet of said reservoir and said inlet of said air pump; and

a head component, said head component comprising a tubular wall and having an inlet, spray apertures, and nozzles releasably connected to said spray apertures, said head component in fluid communication with said air pump, and said tubular wall comprising a filter, wherein said head component is arranged and configured such that said nozzles are spaced apart from the subject.

19. (Re-Presented -- formerly dependent Claim 11) A device for injecting liquids into a subject, said device comprising:

a reservoir for storing a fluid injectate, said reservoir having an inlet and an outlet; an air pump having an inlet and an outlet, said air pump in fluid communication with said reservoir;

at least one injectate filter positioned between said outlet of said reservoir and said inlet of said air pump; and

B¹ a head component, said head component having an inlet, spray apertures, an escape aperture, and nozzles releasably connected to said spray apertures, said head component in fluid communication with said air pump, wherein said head component is arranged and configured such that said nozzles are spaced apart from the subject.

20. (Re-Presented -- formerly dependent Claim 12) The device of Claim 19, further comprising a return line connected to said escape aperture, said return line in fluid communication with said reservoir.

21. (Re-Presented -- formerly dependent Claim 13) The device of Claim 19, further comprising:

a return line connected to said escape aperture; and

a second reservoir, wherein said second reservoir is in fluid communication with said return line and said first reservoir.

22. (Re-Presented -- formerly dependent Claim 14) A device for injecting liquids into a subject, said device comprising:

a reservoir for storing a fluid injectate, said reservoir having an inlet and an outlet;
a plurality of air pumps, each air pump having an inlet and an outlet, and each of said air pumps in fluid communication with said reservoir; and

at least one injectate filter positioned between said outlet of said reservoir and said inlet of said air pump; and

a plurality of head components, each said head components having an inlet, spray apertures, and nozzles releasably connected to said spray apertures, each of said head components in fluid communication with one of said air pumps, wherein said head component is arranged and configured such that said nozzles are spaced apart from the subject.